



HOYLAKE

member of eurotec group

TECHNICAL DATA SHEET

EUROPRIME

Bitumen Solvent Primer

PRODUCT DESCRIPTION

Bitumen primer **EUROPRIMER** is a combination of oil bitumen and a specially selected organic solvents. It has a high penetration ability and short drying time.

AREA OF APPLICATION

The primer is used for preparing (priming) of the substrates (concrete slab, cement-sand screed, etc) before waterproofing with Torch On Membrane or Self Adhesive membrane.

Primer Consumption – 0.3kg/m².

INDICATOR NAME	UNIT	VALUE	TEST METHOD
Density	g/cc	0.85-0.88	ASTM D 70
Penetration at	25°C	2-50 dmm	ASTM D5
Say bolt Fural Viscosity at	25°C	25-1 25	ASTM D 88

PERFORMANCE OF WORKS

Temperature range from -10°C to +40°C. At temperature below +5°C withstand mastic in warm room for at least 24 hours. Drying time under standard conditions is not more than 12 hours.

Do not use near open flame. Work in well-ventilated areas. Avoid contact with skin and eyes.

STORAGE

Keep in a dry place, away from the sun light at temperature from -20°C to +30°C.

Guaranteed shell life – 12 months

PACKAGING INFORMATION

Metal pails 16 kg

NOTE: Every reasonable precaution is taken in the manufacture of all HOYLAKE-products to ensure that they comply with HOYLAKE'S high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all HOYLAKE-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out that oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by HOYLAKE. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered

HOYLAKE TECHNOLOGY PTE LTD, 71 Bukit Batok Crescent, #08-11 The Prestige Centre, 658071, Singapore.
T +65 9632 4488, www.eurotecasia.com